

Nortec-Pro EVO BUS

NEW

TECHNICAL DATA

Vacuum pump	170 l/min
Compressor capacity	600 gr/min
Factor handling (type)	R134a
Tank capacity	30 kg
Oil/additive standard injection	scaled (dosing by oil scales)
Oil tanks	3 (new oil, used, contrast)
Automatic valves	No
Graphic display with icons	4,7" Monochrome
Multilingual software	Yes
Hoses	3m (optional max. 9m)
Database and graphics upgrade of via USB	Yes (free)
Printer	in standard
HP/LP gauges class 1,	Class 1 with working pressure
Tank's pressure gauge	Yes
Moisture filter	Yes
Facilitated charge in each temperature condition with BST system	BST System
Built-in database (cars, industrial vehicles, agricultural machines)	Yes
Leakage test with nitrogen (with kit 01.000.218 on request)	Yes (optional)
Gas analyzer HFO 1234YF set up (with kit on request)	Yes (optional)
Dimensions, cm	50x58,5x113 cm
Weight, kg	100 kg



HIGH CLASS CONNECTORS



OIL TANKS AS STANDARD



CLEAR CONTROL PANEL




PRINTER IN STANDARD



BUILT-IN BRAKE






LARGE WHEELS FOR EASY DRIVING



Multi-language menu!




Simple and intuitive operation

Possibility to create customer databases, detailed printout after the end of the vehicle service process.



The **BST system** allows you to recharge the refrigerant in vehicle air-conditioning systems with the compressor located in the air conditioning station. **It replaces the heating belt** and increases the accuracy recovering gas from the vehicle system by sucking above the minimum pressure.

Extensive vehicle database (passenger, truck and agricultural) with **FREE UPDATE!** You can enter your own custom vehicles into the database. Service of **HYBRID** vehicles.



ABARTH

AUDI

ALFA ROMEO

BMW

DAF TRUCK

MAN

MERCEDES TRUCK


IVECO

AEBI

CAT

JCB

JOHN DEERE



**HANDLE
HOSE FIXINGS**



MANUAL VALVES



TANK GAUGE



**CHECK OIL LEVEL IN
THE COMPRESSOR**



OVERVOLTAGE LIMITER



**ADDITIONAL CONNECTOR KIT
TO BUSES**