

GEO MASTER DYNAMIC I



TECHNICAL DATA



Camera height adjustment: Manual

Camera resolution: 1,3 Megapixel

Wheel compensation: Run out Clamps: 4-points

Tv: Yes screen dimension 32"

Monitor: No Buildin database: Yes Animation 3d with hints: Yes

Compatible: 4-post lift, scissors lift,


canal

Power supply: 230V50Hz

Device for fast and precise measurement of geometry in passenger and delivery vehicles Measurement performed in a three-dimensional system of chassis parameter **modeling** • Image based on precise measuring cameras • 4 passive targets requiring no electronics • Does not require perfectly leveled floor • Intuitive and user-friendly interface • Guidance system with animations on what, where, and how to adjust • Compensation

through vehicle rolling • Camera height manually adjustable • **Multilingual software**, **including** Polish language!





BRAKE AND WHEEL LOCK



TV 32" IN STANDARD



MOUSE AN KEYBOARD TRAY



4-POINTS CLAMPS



ALUMINIUM TURNTABLES











Menu in polish language! Simple and intuitive operation Wide selection of vehicle brands! (including non-standard ones, e.g. ALPINA!)


Adjustment system with intelligent hints along with animations!














Throughout the entire adjustment process we are led by the hand!








MEASURING POSSIBILITIES:

- Total toe, semi-toe axes of the front and rear.
- Camber angle of the front and rear axles
- Caster and camber angle of the steering
- axle misalignment set
- The wheel steering angle, the geometric axis angle of the vehicle
- The difference in toe convergence
- The difference between the wheel camber angle and the steering knuckle caster angle
- A series of other additional measurements, such as wheelbase, track width





OPTIONAL STANDS FOR CLAMPS