


56014A

**DIGITAL METER CONTROL VALVE**

INLET CONNECTOR:
 RANGE OF FLOW RATE:
 RANGE OF PRESSURE REGULATION:
 ACCURACY:
 WORKING TEMPERATURE:
 PUMP TIP:
 POWER SUPPLY:
 WEIGHT:



1/2" BSP
 1 - 25 L / MIN
 3 - 70 BAR
 ± 0.5%
 -10°C - +50°C
 FLEXIBLE - WITH A SEMI-AUTOMATIC TIP
 1 BATERIA 3V
 1.5 kg

**NOZZLE TIP****LCD DISPLAY****OIL HOSE 4 M****OIL PUMP**

RATIO OF PRESSURES:
 MAX. PERFORMANCE:
 WORKING PRESSURE:
 AIR INTAKE CONNECTOR:
 OIL OUTLET CONNECTORS:
 LENGTH SUCTION TUBE
 DIAMETER OF SUCTION PIPE:
 APPLIANCE:
 WEIGHT:

5:1
 OD 10 DO 14 L/MIN (in acc. type of oil)
 30~40 BAR
 1/4 "QUICK COUPLING
 1/2 "MALE QUICK COUPLING
 940 mm
 37 mm
 ENGINE AND TRANSMISSION OILS
 8 kg

**HEAD PUMP****AIR INTAKE VALVE****OIL SCREEN (FILTER)****BARREL TROLLEY**

WHEEL:
 SAFETY:
 CAPACITY:

2 LARGE FULL, 2 SMALL TORSION
 CHAIN OF SAFETY. BARREL
 200 KG

**PUMP HOLDER****LARGE FULL WHEELS****SMALL SWIVEL WHEELS**