

WASTE OIL CHANGER

AIR PRESSURE (7-8 bar) INCLUDES 6 SUCTION PROBES (METAL AND FLEXIBLE) OIL LEVEL INDICATOR EMPTYING OF PRESSURE OR GRAVITY

99291:30L 99294:65L 99293:90L



OIL LEVEL INDICATOR EMPTYING OF PRESSURE (max. 1 bar)

CAPACITY OF THE SINK: 18L

ADJUSTABLE HEGHT OF SINK: 1150 mm - 1850 mm

MODEL: CAPACITY

2065:65L 10950:90L



AIR PRESSURE (7-8 bar) INCLUDES 6 SUCTION PROBES (METAL AND FLEXIBLE) EMPTYING PRESSURE (max. 1 bar) CAPACITY OF THE CONTROL TANK: 8 L

MODEL: CAPACITY

NORTEC

2365:65L 10925:90L



WASTE OIL DRAINER

AIR PRESSURE (7-8 bar) INCLUDES 6 SUCTION PROBES (METAL AND FLEXIBLE) OIL LEVEL INDICATOR EMPTYING OF PRESSURE (max. 1 bar) CAPACITY OF THE SINK: 18L TANK CAPACITY: 90L



WASTE OIL DRAINER/CHANGER WITH CHAMBER

AIR PRESSURE (7-8 bar) INCLUDES 6 SUCTION PROBES (METAL AND FLEXIBLE) OIL LEVEL INDICATOR EMPTYING OF PRESSURE (max. 1 bar) CAPACITY OF THE CONTROL TANK: 8L CAPACITY OF THE SINK: 18L TANK CAPACITY: 90L

MODEL: 10900

