








PD5500TOP

CAPACITY:	5500 kg
POWER SUPPLY:	400V/50Hz
MOTOR POWER:	2,2 kW
LIFTING HEIGHT:	1949 mm
MACHINE HEIGHT:	5420 mm
CLEARANCE:	2906 mm
3-STAGE ARMS:	820 -1950 mm
OIL PRESSURE:	16 MPa
NOISE LEVEL:	<80 dB

Baseless electrohydraulic 2 post lift ♦ Mechanical synchronization
 ♦ electromagnetic height lock ♦ automatic arm lock during lifting
 ♦ Adjustable upper traverse in the range of 5200 / 5320 / 5420 mm
 ♦ set of door protection.



PD5500TOP



WYMIARY POSADZKI: 5200x1800mm

INSTALLATION REQUIREMENTS:



Concrete class: B25 or C20 / 25 with a minimum mounting area: 5200x1800x300mm ♦ Acceptable floor imbalance: +/- 5mm, floor execution: 3 weeks before assembly ♦ Mounting anchors: mechanical M18 / 160 mm 14 pieces or chemical M16 / 250mm ♦ Hydraulic oil: HL22, 18.0l ♦ Power supply: 5x2.5mm cable to the place of assembly ♦ Current protection: min. 32A with 3-phase 400V / 50Hz power supply.

Installation allowed only in closed areas ♦ prohibition of using reinforcement 20 cm from the top thicker than 4mm² ♦ assembly for chemical anchors for an additional fee (submit in advance, preferably when setting the date of assembly) ♦ All connections, with particular reference to electrical connections, they must be made by authorized persons ♦ The installation must remain carried out by qualified personnel according to the rules attached in this building plan ♦ In the case of assembly by Nortec or its authorized service center, the lift must be on solid ground.